

Product Identifier:	MICA	
Other Means of Identification:	Potassium Aluminum Silicate (Muscovite)	
Product Family:	Lost Circulation Material	
Recommended Use:	Drilling Fluid Additive	
Manufacturer/Supplier:	Bri-Chem Supply Ltd. 27075 Acheson Road Acheson, AB T7X 6B1	
Phone Number:	780-962-9490	
Emergency Phone:	CHEMTREC 1-800-424-9300, 24/7	
Section 2: HAZARD(S) IDENTIFICATION		
Classification:	Carcinogenicity 1A; Specific target organ toxicity (repeated exposure) – Category 2	
Label Elements:		
Signal Word:	Danger	
Hazard Statement(s):	May cause cancer. May cause damage to organs through prolonged or repeated exposure.	
Precautionary Statement(s)		
Prevention:	Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Wear protective gloves/protective clothing/eye protection/face protection.	
Response:	If exposed or concerned: Get medical advice or attention.	
Storage:	Store locked up	
Disposal:	Dispose of contents and container in accordance with local regional, national and international regulations.	
Section 3: COMPOSITION / INFORMATION ON INGREDIENTS		

Chemical Name	CAS No.	%	Other Identifiers	Other Names
Міса	12001-26-2	98-100		
Silica, Quartz	14808-60-7	1-2		



SAFETY DATA SHEET	
	Section 4: FIRST-AID MEASURES
First-Aid Measures	
Inhalation:	Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial resuscitation. If irritation develops or persists, seek medical attention.
Skin Contact:	Wash with soap and water. If adverse symptoms develop, seek medical attention.
Eye Contact:	Immediately rinse the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open. If eye irritation develops or persists, seek medical attention.
Ingestion:	Give large quantities of water to induce vomiting. Never give anything by mouth to an unconscious or convulsing victim. Get medical attention, if adverse symptoms develop.
;	Section 5: FIRE-FIGHTING MEASURES
Extinguishing Media	
Suitable Extinguishing Media:	Dry chemical, carbon dioxide, foam, water.
Specific Hazards Arising from The Product:	Non-flammable
Special Protective Equipment and Precautions for Fire-Fighters:	A solid stream of water or foam directed into hot, burning liquid can cause frothing. Firefighters must wear appropriate breathing apparatus and clothing.
Secti	ion 6: ACCIDENTAL RELEASE MEASURES
Personal Precautions, Protective Equipment, and Emergency Procedures:	Use the personal protective equipment recommended in Section 8 of this safety data sheet
Environmental Precautions:	It is good practice to prevent releases into the environment. Do not allow into any sewer, on the ground or into any waterway.
Methods and Materials	Use appropriate safety equipment. Small spill: sweep up and put into approved DOT containers for disposal or re-use.

Large spill: DO NOT allow to enter waterways; sweep or shovel into approved DOT containers for disposal or re-use.



Section 7: HANDLING AND STORAGE		
Precautions for Safe Handling:	Avoid ingestion. Practice reasonable caution and personal cleanliness. Avoid contact with skin and eyes. Handle in accordance with good industrial hygiene and safety practice. It is good practice to: avoid breathing product; avoid skin and eye contact and wash hands after handling.	
Conditions for Safe Storage:	Store in a cool, dry, well-ventilated place. Keep container tightly closed and away from incompatible materials.	

### Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Міса		
ACGIH TLV:	3 mg/m³ respirable	
OSHA PEL:	20 mppcf	
Silica Quartz		
ACGIH TLV TWA:	0.025 mg/m³ respirable fraction	
OSHA PEL TWA:	0.1 mg/m³	
OSHA PEL:	Respirable Quartz: 10 mg/m <sup>3</sup> divided by the value of "%SiO2 + 2"	
	Total Quartz: 30 mg/m <sup>3</sup> divided by the value of "%SiO2 + 2"	
ACGIH®:	American Conference of Governmental Industrial Hygienists.	
TLV®:	Threshold Limit Value	
OSHA:	US Occupational Safety and Health Administration	
PEL:	Permissible Exposure Limits	
TWA:	Time-Weighted Average	
Appropriate Engineering Controls:	Provide mechanical ventilation to prevent dust concentrations and to reduce potential exposure.	
Individual Protection Measures		
Eye/Face Protection:	Wear chemical safety goggles	
Skin Protection:	Chemical-resistant clothing is recommended including glove, apron and goggles.	
Respiratory Protection:	Wear a NIOSH approved air-purifying respirator with an appropriate cartridge.	

### Section 9: PHYSICAL AND CHEMICAL PROPERTIES

### **Basic Physical and Chemical Properties**

Appearance:	Grey – black shiny flakes. Particle size: Not available
Odour:	Odourless
pH:	7 – 8



SAFETY DATA SHEET	
Flash Point:	Not available
Evaporation Rate:	Not available
Upper/Lower Flammability or Explosive Limit:	Not available (upper); Not available (lower)
Relative Density (Water=1):	2.7 – 2.9
Solubility:	Insoluble in water; Not available (in other liquids)
Auto-ignition Temperature:	Not available
Decomposition Temperature:	Not available
Other Information	
Physical State:	Solid
Bulk Density:	Not available

Section 10: STABILITY AND REACTIVITY		
Chemical Stability:	Normally stable	
Possibility of Hazardous Reactions:	Hazardous polymerization will not occur.	
Incompatible Materials:	Strong acids (e.g. hydrochloric acid). Alkalis.	
Hazardous Decomposition Products:	Above 1100°C minor quantities of fluorides may evolve.	

Likely Routes of Exposure:	Skin contact; eye contact; inhalation	
Skin Corrosion/Irritation:	No irritation expected	
Serious Eye Damage/Irritation:	Contact may cause mechanical irritation and possible injury. Individuals subject to eye irritation should not be exposed to crystalline silica dust.	
STOT (Specific Target Organ Toxicity) – Single Exposure		
Inhalation:	Irritation of respiratory tract, nose and throat due to dust. Individuals with respiratory disease, including but not limited to asthma and bronchitis should not be exposed to crystalline silica dust.	
Ingestion:	No adverse effects expected for normal, incidental ingestion.	

# Mica (F,M,C)



### STOT (Specific Target Organ Toxicity) – Repeated Exposure

	This product has the potential for generation of respirable dust during handling and use. Dust may contain respirable crystalline silica. Overexposure to dust may result in pneumocononiosis, a respiratory disease causes by inhalation of mineral dust, which can lead to fibrotic changes to the lung tissue, or silicosis, a respiratory disease by inhalation of silica dust, which can lead to inflammation and fibrosis of the lung tissue. Silicosis: Excessive inhalation of respirable crystalline silica dust may cause a progressive, disabling, and sometimes fatal lung disease called silicosis. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness, and reduced pulmonary function. This disease is exacerbated by smoking. Individuals with silicosis are predisposed to develop tuberculosis.
Carcinogenicity	
Silica Quartz	
IARC:	Group 1
ACGIH:	A2
NTP:	Known human carcinogen
Key to Abbreviations	
IARC:	International Agency for Research on Cancer
Group 1:	Carcinogenic to humans
ACGIH®:	American Conference of Governmental Industrial Hygienists
A2:	Suspected human carcinogen
NTP:	National Toxicology Program

No information was located for: Respiratory and/or Skin Sensitization, Development of Offspring, Sexual Function and Fertility, Germ Cell Mutagenicity, Interactive Effects

## Section 12: ECOLOGICAL INFORMATION

No ecotoxicity or environmental fate data available. It is good practice to prevent releases into the environment.

### Section 13: DISPOSAL CONSIDERATIONS

Disposal Methods:	Dispose of in accordance with federal, provincial and local
	government regulations. Containers should NOT be re-used.
	Containers should be disposed of in accordance with
	government guidelines.



### SUPPLY LTD

SAFETY DATA SHEET

#### Section 14: TRANSPORT INFORMATION

Not regulated under Canadian TDG Regulations.

**Special Precautions:** Not applicable

Transport in Bulk According Not applicable to Annex II to MARPOL 73/78 and the IBC Code:

#### Section 15: REGULATORY INFORMATION

Safety, Health and Environmental Regulations

Canada

WHMIS 1988 Classification:



Class D2A – Very Toxic

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all of the information required by the Controlled Products Regulations.

#### Section 16: OTHER INFORMATION

#### **Disclaimer:**

The information contained herein is based on data available to us and is believed to be true and accurate. However, no guarantee or warranty is provided, expressed or implied, by the company or its subsidiaries regarding accuracy of the information, the hazards connected with the use of the material, or the results to be obtained from the use thereof. Since the use of this product is within the exclusive control of the user, we do not assume any responsibility and expressly disclaim any liability for any use of this product. It is the user's responsibility to determine the conditions of safe use, storage, and disposal of the product. Compliance with all applicable federal, provincial, and local regulations remains the responsibility of the user.

Prepared by: Bri-Chem Supply Ltd. **Revision Date:** July 16, 2024

Mica (F,M,C)